

Keling High Torque Stepper Motor



Detailed Electrical Specification:

NEMA17 Series:

<i>Series</i>	<i>Length (mm)</i>	<i>Peak Torque (oz-in)</i>	<i>Shaft Diameter (in)</i>	<i>Weight (kg)</i>
<i>KL17H247-168-4B</i>	47.5	61.6	1/5	0.35

NEMA23 Series

<i>Series</i>	<i>Length (mm)</i>	<i>Peak Torque (oz-in)</i>	<i>Shaft Diameter (in)</i>	<i>Weight (kg)</i>
<i>KL23H2100-30-4BM</i>	100	495	1/4	
<i>KL23H2100-30-4B</i>	100	382	1/4	
<i>KL23H2100-35-4B</i>	100	318	1/4	1.5
<i>KL23H286-20-8B</i>	88	425	1/4	1.4
<i>KL23H284-35-4B</i>	84	318	1/4	1.1
<i>KL23H276-30-8B</i>	76	282	1/4	1.0
<i>KL23H276-30-8A</i>	76	282	1/4	1.0
<i>KL23H276-28-4B</i>	76	282	1/4	1.0
<i>KL23H276-30-6A</i>	76	282	1/4	1.0
<i>KL23H276-30-4A</i>	76	282	1/4	1.0
<i>KL23H256-21-8B</i>	56	185	1/4	0.7
<i>KL23H251-24-8B</i>	51	156	1/4	0.65

NEMA34 Series:

<i>Series</i>	<i>Length (mm)</i>	<i>Peak Torque (oz-in)</i>	<i>Shaft Diameter (in)</i>	<i>Weight (kg)</i>
<i>KL34H2160-62-8A</i>	156	1810	1/2	5.6
<i>KL34H2160-62-8B</i>	156	1810	1/2	5.6
<i>KL34H2160-62-4A</i>	156	1200	1/2	5.6
<i>KL34H2120-42-8B</i>	118	1200	1/2	3.8
<i>KL34H2120-42-8A</i>	118	1200	1/2	3.8
<i>KL34H2120-60-4A</i>	118	1200	1/2	3.8
<i>KL34H2120-60-4B</i>	118	1200	1/2	3.8
<i>KL34H295-43-8B</i>	96	906	1/2	2.3
<i>KL34H295-43-8A</i>	96	906	1/2	2.3
<i>KL34H295-61-4A</i>	96	906	1/2	2.3
<i>KL34H280-45-4A</i>	78	640	1/2	2.4
<i>KL34H280-60-4A</i>	80	640	1/2	2.3
<i>KL34H280-60-4B</i>	80	640	1/2	2.3
<i>KL34H280-45-8A</i>	78	640	1/2	2.4
<i>KL34H280-45-8B</i>	78	640	1/2	2.4
<i>KL34H280-55-4A</i>	78	637	1/2	2.4
<i>KL34H260-42-8A</i>	60	400	1/2	1.7
<i>KL34H260-42-8B</i>	60	400	1/2	1.7
<i>KL34H260-60-4A</i>	60	465	1/2	1.7
<i>KL34H260-60-4B</i>	60	465	1/2	1.7

NEMA42 Series:

<i>Series</i>	<i>Length (mm)</i>	<i>Peak Torque (oz-in)</i>	<i>Shaft Diameter (in)</i>	<i>Weight (kg)</i>
<i>KL42H2150-42-8A</i>	150	2830	0.63	8.4
<i>KL42H2150-42-8B</i>	150	2830	0.63	8.4